

1080P FULL-HD 23X ZOOM 656' IR WDR DAY/NIGHT OUTDOOR PTZ SPEED DOME IP CAMERA

Ultra-low-light technology enables the PTZ camera to see up to 656' in the dark

- + 1920 x 1080 (1080p) -HD video resolution @ 30 fps
- + 23x optical zoom and 16x digital zoom
- + This camera features Advanced Infrared Technology, which includes:
 - Smart IR reduces over-exposure of the IR LEDs at the center of the image
 - Full Frame Illumination produces a wider illumination spread and reduces video noise, while reducing bandwidth consumption
- + Ultra-low-light technology enables the camera see up to 656' in the dark
- + True day/night (ICR) captures sharp, detailed images day and night
- + Enhanced imaging with True WDR and 3D-DNR
- + Smart auto tracking detects and tracks progressively moving objects within the camera's coverage area
- + 360° continuous rotation and -20°~90° tilt
- + IP66 weather rated
- + ONVIF Profile S compliant and ONVIF Profile G approved
- + Operates on 24 Vac or via high-PoE midspan injector
- + Micro SD card slot supports up to 128GB micro SD cards
- + Free Alibi Witness iOS/Android mobile app



IP

What's Included

+ High-PoE midspan injector

1080

- + Mounting template
- + Set mounting hardware
- + CD ROM (User's guide and installation tools)
- + Quickstart guide

FEATURES



Megapixel Resolution – Cover more area and see more detail. Megapixel cameras can cover a larger area without compromising image quality. Megapixel resolution cameras deliver high-definition images with much greater detail. They are ideal where a greater level of detail is needed, such as for facial recognition and license plate identification. **Auto Tracking** – Detect and track activity. The camera's smart auto tracking feature detects and tracks progressively moving objects within the camera's coverage area.



Smart IR – Captures clear, sharp images in low light. Smart IR (smart infrared) automatically adjusts the amount of infrared light used to illuminate a scene as the subject moves closer to or further away from the camera, resulting in optimal exposure and a sharp, clear image that is neither washed out or too dark.



1080p Full-HD 23x Zoom 656' IR WDR Day/Night Outdoor PTZ Speed Dome IP Camera

FEATURES

Full Frame Illumination – Illuminates more area. Full Frame Illumination (FFI) delivers a wider IR illumination spread and produces a brighter, clearer picture in low light and at night – without hot spots. FFI reduces video noise, for a clearer image, along with reducing bandwidth consumption and video storage requirements.



3D Digital Noise Reduction (3D-DNR) – Get exceptional video image quality with less noise. 3D-DNR incorporates frame-to-frame noise reduction with spatial noise reduction to produce clear video images with less noise, in low light conditions. Noise reduction is critical for video because noise affects image quality. Cameras with 3D-DNR produce sharper, more accurate video images.

True Wide Dynamic Range (WDR) – Gain better images in diverse lighting conditions. This feature enables the camera to take multiple images while capturing video at different exposure levels. It combines the images for the best balance, and compensates for lights and darks for perfectly exposed images in both bright and shadowed areas of a diversely lit scene True WDR also reduces video noise.

True Day/Night (ICR) – Enjoy around-the-clock surveillance. Our day/night cameras with true day/night (ICR) deliver a sharp image in low light and nighttime conditions. An IR cut filter blocks out infrared light to produce true-to-life color images during the daytime. In low light conditions and at night, the filter is removed, letting infrared light pass through to provide crisp, well-defined black and white images.

Camera Motion Detection – Get a visual alert. This feature provides a visual indicator on the monitoring screen when motion is detected within the camera's field of view, so that an operator is quickly alerted when activity is detected.

Privacy Zone Masking – Keep desired areas private. This feature enables you to set zones for select areas within the camera's field of view, that need to be excluded when viewing and recording video. These areas are overlaid with a privacy mask so that video of the specified zones cannot be viewed or recorded.



Free Alibi Witness iOS/Android App – View your video remotely from anywhere. Enjoy convenient remote access from your iOS or Android device with a FREE app.

ONVIF Profile S Compliant – Enjoy greater compatibility with more devices. This product conforms to ONVIF (Open Network Video Interface Forum) specifications for IP-based security products. ONVIF defines a common protocol for the exchange of information between different network video devices from different manufacturers, to allow greater interoperability in multi-vendor network video systems.



SPECIFICATIONS

CAMERA		OPTIONAL ACCESSORIES
Image Sensor	1/1.9" CMOS	
Scanning Mode	Progressive Scan	
Resolution	Up to 1920 x 1080	
Effective Pixels	Approx. 2.1 Megapixel	
Minimum Illumination	Color: 0.02 Lux (F1.6, AGC On)	and the second s
	B/W: 0.002 Lux, 0 Lux (IR ON)	Jacob Contraction of
Day/Night	True Day/Night ICR	ALI-PTZWB Wall Mount Bracket
Wide Dynamic Range	120 dB	
Electronic Shutter (sec)	1 ~ 1/30,000	
Gain Control	Auto/Manual	
White Balance Mode	Auto/Manual/ATW/Indoor/Outdoor/Daylight Lamp/ Sodium Lamp	
Noise Reduction	3D DNR	
IR Illuminators	Smart IR Array, Adjustable by zoom, 850nm	
IR Array Range	656 ft	ALI-PTZCM PTZ Corner Mount Bracket
IR Sensitivity	700 - 1100nm	
Panning Range and Speed	0° ~ 360° endless, Max 160°/Sec	
Tilting Range and Speed	-20° ~ 90°, Max 120°/Sec	2 4
LENS		
Lens Type	Varifocal	e))
Focal Length	5.9 ~ 135.7 mm	1. 2
Iris	Auto	ALI-PTZCL
Focus	Auto/Semiautomatic/Manual	PTZ Ceiling Mount Bracket
Horizontal Viewing Angle	59.8° (Wide) ~ 3.0° (Tele)	
F-number	F1.5 ~ F3.4	
VIDEO		۲.
Video Compression Format	H.264 (Baseline/Main/High Profile), MPEG-4, MJPEG	G .
Codec Streaming Capability	Tri Streaming	6
Maximum Frame Rate	30fps @ 1080p	
Bit Rate	32 kbps ~ 16 Mbps	ALI-PTZPM Outdoor Pole Mount Bracket
Bit Rate Mode	CBR, VBR	
AUDIO		
Audio Streaming	Two-way	_
Audio Compression Format	G.711ulaw/G.711alaw/G.726/MP2L2/G.722	6
PAN AND TILT		
Smart Tracking	Manual/ Panorama/ Intrusion trigger/ Line crossing	U.
	trigger/ Region entrance trigger/Region exiting trigger/ Smart tracking when patrol between multiple scenarios	ALI-PTZPPT Outdoor Parapet Roof Mount
Number of Presets	300	
Patrol	8 Patrols, Up to 32 presets per patrol	
Pattern	4 Patterns	
PTZ Position Display	On/Off	
	'	



SPECIFICATIONS

FEATURES		
Motion Detection	Yes	
Event Notification	Alarm Output, Email, FTP	
Privacy Mask	Yes	
ROI Encoding	Up to 24 areas with adjustable levels	
Defog	Yes	
Video Analytics	Face detection, Intrusion detection, Line crossing detection, Region entrance, Region exiting, Audio exception detection, Tamper Detection	
INTERFACE		
Ethernet	RJ-45 10/100 BASE-T	
Audio Input	1x In	
Audio Output	1x Out	
Sensor Input	7x In	
Alarm Ouput	2x Out	
SD Card Slot	1x SD/SDHC/SDXC (up to 128GB)	
Video Output	1x BNC	
NETWORK	·	
Protocols	IPv4/IPv6, HTTP, HTTPS, 802.1x, Qos, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, ICMP, DHCP, PPPoE, ONVIF, PSIA	
Security	User authentication (ID and PW), Host authentication (MAC address), IP address filtering	
Network Storage	NAS (Support NFS, CIFS/SMB)	
GENERAL		
Power Requirements	High-PoE / 24 Vac	
Power Consumption	High-PoE: Max. 30 W (Heater Off) / Max. 50 W (Heater On) 24 Vac: Max. 20 W (Heater Off) / Max. 65 W (Heater On)	
Weight	17.63 lbs.	
Dimensions	16.52" H x 10.49"	
operating Temperature	-40°F ~ 149°F	
operating Temperature Operating Humidity		
Operating Humidity	-40°F ~ 149°F 0% ~ 90% RH, Non-condensing IP66	
	0% ~ 90% RH, Non-condensing IP66	
Operating Humidity Ingress Protection Color	0% ~ 90% RH, Non-condensing IP66 Beige/Black	
Operating Humidity Ingress Protection Color Material	0% ~ 90% RH, Non-condensing IP66 Beige/Black Aluminum (Body) / Polycarbonate (Lens Cover)	
Operating Humidity Ingress Protection Color Material Approvals	0% ~ 90% RH, Non-condensing IP66 Beige/Black	
Operating Humidity Ingress Protection Color Material Approvals SYSTEM REQUIREMENTS	0% - 90% RH, Non-condensing IP66 Beige/Black Aluminum (Body) / Polycarbonate (Lens Cover) CE, FCC, RoHS	
Operating Humidity Ingress Protection Color Material Approvals SYSTEM REQUIREMENTS Operating System	0% ~ 90% RH, Non-condensing IP66 Beige/Black Aluminum (Body) / Polycarbonate (Lens Cover) CE, FCC, RoHS Windows XP/VISTA/7/8/10, Mac OSX	
Operating Humidity Ingress Protection Color Material Approvals SYSTEM REQUIREMENTS Operating System Processor	0% - 90% RH, Non-condensing IP66 Beige/Black Aluminum (Body) / Polycarbonate (Lens Cover) CE, FCC, RoHS Windows XP/VISTA/7/8/10, Mac OSX Intel Pentium 4 3.0 GHz or later	
Operating Humidity Ingress Protection Color Material Approvals SYSTEM REQUIREMENTS Operating System Processor Memory	 0% ~ 90% RH, Non-condensing IP66 Beige/Black Aluminum (Body) / Polycarbonate (Lens Cover) CE, FCC, RoHS Windows XP/VISTA/7/8/10, Mac OSX Intel Pentium 4 3.0 GHz or later 1 GB or above RAM 	
Operating Humidity Ingress Protection Color Material Approvals SYSTEM REQUIREMENTS Operating System Processor Memory Display	 0% - 90% RH, Non-condensing IP66 Beige/Black Aluminum (Body) / Polycarbonate (Lens Cover) CE, FCC, RoHS Windows XP/VISTA/7/8/10, Mac OSX Intel Pentium 4 3.0 GHz or later 1 GB or above RAM 1024 x 768 resolution or higher 	
Operating Humidity Ingress Protection Color Material Approvals SYSTEM REQUIREMENTS Operating System Processor Memory	 0% - 90% RH, Non-condensing IP66 Beige/Black Aluminum (Body) / Polycarbonate (Lens Cover) CE, FCC, RoHS Windows XP/VISTA/7/8/10, Mac OSX Intel Pentium 4 3.0 GHz or later 1 GB or above RAM 1024 x 768 resolution or higher Internet Explorer 6.0 or above, Apple Safari 5.02 or above, 	
Operating Humidity Ingress Protection Color Material Approvals SYSTEM REQUIREMENTS Operating System Processor Memory Display Web Browser	 0% - 90% RH, Non-condensing IP66 Beige/Black Aluminum (Body) / Polycarbonate (Lens Cover) CE, FCC, RoHS Windows XP/VISTA/7/8/10, Mac OSX Intel Pentium 4 3.0 GHz or later 1 GB or above RAM 1024 x 768 resolution or higher Internet Explorer 6.0 or above, Apple Safari 5.02 or 	
Operating Humidity Ingress Protection Color Material Approvals SYSTEM REQUIREMENTS Operating System Processor Memory Display	 0% - 90% RH, Non-condensing IP66 Beige/Black Aluminum (Body) / Polycarbonate (Lens Cover) CE, FCC, RoHS Windows XP/VISTA/7/8/10, Mac OSX Intel Pentium 4 3.0 GHz or later 1 GB or above RAM 1024 x 768 resolution or higher Internet Explorer 6.0 or above, Apple Safari 5.02 or above, Mozilla Firefox 3.5 or above 	
Operating Humidity Ingress Protection Color Material Approvals SYSTEM REQUIREMENTS Operating System Processor Memory Display Web Browser	 0% - 90% RH, Non-condensing IP66 Beige/Black Aluminum (Body) / Polycarbonate (Lens Cover) CE, FCC, RoHS Windows XP/VISTA/7/8/10, Mac OSX Intel Pentium 4 3.0 GHz or later 1 GB or above RAM 1024 x 768 resolution or higher Internet Explorer 6.0 or above, Apple Safari 5.02 or above, 	